



Preliminary Product Information Sheet Solar Module BSP60/65-12

General Information

High performance multi-crystalline cells
High energy yields in a wide variety of climates
Anodized aluminum frame provides for easy mounting

Qualification and Certificates

UL Listing Pending

Electrical Characteristics

| Typical Data At STC | | | |
|-----------------------|------|----------|----------|
| | | BSP60-12 | BSP65-12 |
| Rated Power | Pr | 60W | 65W |
| Peak Power | Pmpp | 60W | 65W |
| Peak Power Voltage | Vmpp | 16.9V | 17.4V |
| Peak Power Current | Impp | 3.55A | 3.75A |
| Open Circuit Voltage | Voc | 21.5V | 21.7V |
| Short Circuit Current | Isc | 3.73A | 3.99A |

The performance of the solar cells is measured at Standard Test Conditions (STC): 1000 W/m² irradiance, AM 1.5 spectrum and 25° C cell temperature.

Physical Characteristics

| | | |
|-----------|-------------|----------------|
| Length | Inches (mm) | 58.0 (1473.2) |
| Width | Inches (mm) | 13.75 (349.25) |
| Thickness | Inches (mm) | 1.75 (44.4) |

| | | |
|-------------------|-----------|--------------|
| Cable Type | 18/2 | |
| Cable Length | feet (cm) | 15.0 (457.2) |

10 Year Warranty

