

24V300A-8D-CTRL400 Deep Cycle+Engine Start Lithium Battery

Battery Specification

Attribute		Value
Nominal True Capacity	300	Amp Hours
Charging Voltage	28.0 to 28.4	Volts
Nominal Voltage	25.6	Volts
Cut-off Discharge Voltage	23.6	Volts
Max Discharge Current (Continuous)	400	Amps
Max Discharge Current (1sec pulse)	2000	Amps
Max Continuous Charge Current	400	Amps
Internal Impedance	< 8	Milliohms
Cycle Life @ 80% Depth of Discharge	2000-3000	
Dimensions (L x W x H)	23.0 x 13.1 x 11.8	Inches
Weight	145	Pounds
Safety Leader U.N. International Approved	U.N. D.O.T. 38.3	Lithium
Charge Temperature	32 to 113	Fahrenheit
Discharge Temperature	-4 to 140	Fahrenheit
Storage Period (1 month)	-4 to 113	Fahrenheit
Storage Period (6 month)	-4 to 77	Fahrenheit
Battery Terminals (Max Torque 100in-lbs)	1/2"	Brass Bolt
Lithionics NeverDie Feature	YES	
Active Shunt Cell Balancing	YES	
Wireless NeverDie Remote	YES	Optional

NOTE: Contact Lithionics Battery for a user installation Guide. Follow the guide to ensure fitness of use and warranty.

24V300A-8D-CTRL400





7500Wh
145LBS

WHY CHOOSE, JUST
Give me the ION!

NeverDie Features

- Reserve Capacity (Low Voltage Cutoff @ 23.6V)
- Pushbutton Storage Option
- Active Shunt Cell Balancing
- Individual Cell Monitoring (Temp & Voltage)
- Charge Enable (25.0V)
- Overtemp Protection (Enabled @ 140F/60C)
- Over-Discharge Protection (Dead Voltage Lockout @ 20V)
- Short Circuit Protection



PROPRIETARY AND CONFIDENTIAL. THE INFORMATION IN THIS DRAWING IS THE SOLE PROPERTY OF LITHIONICS. ANY REPRODUCTION IN PART OR WHOLE WITHOUT WRITTEN PERMISSION FROM LITHIONICS IS PROHIBITED.

Main Office: 855-726-4204
or send an email to info@lithionicsbattery.com

www.lithionicsbattery.com